

SAE 20W60 WOLTEC PREMIUM OIL

Performance Standard: API SF/SJ/SL/SM/SN

Product Description: WOLTEC PREMIUM GASOLINE OILS are formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. It has been specifically engineered with cleansing technology to stop dirt and sludge build up and therefore help protect and prolong the life of the engine.

Features and Benefits

Features	Advantages and Potential Benefits
Meets or exceeds demanding specifications of major OEMs	One engine oil for mixed fleet operations
Outstanding thermal and oxidation stability	Control of low temperature sludge build-up and high temperature deposits
Low volatility, excellent wear and bore polish control	Good oil consumption control
Expertly formulated low viscosity formulation	Fuel economy potential(1)
Good resistance to corrosion	Helps towards long life of critical wear surfaces
Long drain capability	Help towards operational efficiency and overall cost control
Component compatibility	Long gasket and seal life, extended service intervals

TYPICAL PROPERTIES:

SL NO	TEST PARAMETERS	TEST METHODS	UNITS	RESULTS**
1	Appearance	Visual	NONE	Bright & Clear
2	Color	ASTM D 1500-12	NONE	Report
3	Total Base Number	ASTM D 2896	mg KOH/g	9.85
4	Density @ 15°C	ASTM D 4052-11	g/ml	0.894
5	Kinematic Viscosity @ 40 °C	ASTM D 445	cSt	226.01
6	Kinematic Viscosity @ 100 °C	ASTM D 445	cSt	24.8
7	Viscosity Index	ASTM D 2270	NONE	131
8	Pour Point	ASTM D 97	°C	-21
9	CCS @ -15°C	ASTM D 5293	cP	9900
10	Flash Point	ASTM D 92	°C	240

(**The features mentioned above are average values obtained with some variability in production and do not constitute a specification)

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.